

FG 06**Safety Data Sheet**

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Code: **1704010024**
Product name **FG 06**
UFI : **63D0-A01W-800J-X9UC**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Hydrophobic fine mortar for exteriors**

Identified Uses	Industrial	Professional	Consumer
BUILDING	-	SU: 19.	SU: 19.

**Product to be mixed with water for application on buildings.
Product for craft and private use.
Any other use is not recommended.**

1.3. Details of the supplier of the safety data sheet

Name **FORNACI CALCE GRIGOLIN S.p. A.**
Full address **Via Foscarini, 2**
District and Country **31040 Nervesa della Battaglia (TV)**
Italy
Tel. **+39 0422 5261**
Fax **+39 0422 526299**

e-mail address of the competent person responsible for the Safety Data Sheet **info@fornacigrigolin.it**

1.4. Emergency telephone number

For urgent inquiries refer to **HEALTH EMERGENCY - 112**

SECTION 2. Hazards identification**2.1. Classification of the substance or mixture**

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Serious eye damage, category 1	H318	Causes serious eye damage.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Skin sensitization, category 1B	H317	May cause an allergic skin reaction.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



FG 06**SECTION 2. Hazards identification ... / >>**

Signal words: Danger

Hazard statements:

H318 Causes serious eye damage.
H315 Causes skin irritation.
H335 May cause respiratory irritation.
H317 May cause an allergic skin reaction.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P261 Avoid breathing dust.
P280 Wear protective gloves / face protection.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER / doctor / . . .
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Contains: PORTLAND CEMENT CLINKER
HYDRATED LIME

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

The mixture has a low chromate content. After adding water the soluble chromium (VI) content is at most 2 ppm on the dry product.

To maintain a low chromate content, store it properly, in dry conditions, respecting the maximum expected storage terms.

The percentage of respirable crystalline silicon oxide is less than 1%. Therefore the product is not subject to identification. However it is advisable to use respiratory protection.

SECTION 3. Composition/information on ingredients**3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
HYDRATED LIME		
INDEX	$15 \leq x < 25$	Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335
EC	215-137-3	
CAS	1305-62-0	
REACH Reg.	01-2119475151-45-0267	
PORTLAND CEMENT CLINKER		
INDEX	$3 \leq x < 8$	Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, Skin Sens. 1B H317
EC	266-043-4	
CAS	65997-15-1	
REACH Reg.	02-2119682167-31-0000	

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

SECTION 4. First aid measures ... / >>

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products. The product is combustible and, when the powder is released into the air in sufficient concentrations and in the presence of a source of ignition, it can create explosive mixtures with air. Fires may start or get worse by leakage of the solid product from the container, when it reaches high temperatures or through contact with sources of ignition.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

If there are no contraindications, spray powder with water to prevent the formation of dust.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product and place it in containers for recovery or disposal. If there are no contraindications, use jets of water to eliminate product residues.

Make sure the leakage site is well aired. Evaluate the compatibility of the container to be used, by checking section 10. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

SECTION 7. Handling and storage ... / >>

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2022

HYDRATED LIME

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLEP	FRA	5				
GVI/KGVI	HRV	5				
WEL	GBR	5				
OEL	EU	5				
TLV-ACGIH		5				

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,49	mg/l
Normal value in marine water	0,32	mg/l
Normal value for water, intermittent release	0,49	mg/l
Normal value of STP microorganisms	3	mg/l
Normal value for the terrestrial compartment	1080	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Effects on workers					
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation	4		1		4		1	
	mg/m3		mg/m3		mg/m3		mg/m3	

PORTLAND CEMENT CLINKER

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH		1				RESP

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ;

MED = medium hazard ; HIGH = high hazard.

During the risk assessment process, it is essential to take into consideration the ACGIH occupational exposure levels for inert particulate not otherwise classified (PNOC respirable fraction: 3 mg/m3; PNOC inhalable fraction: 10 mg/m3). For values above these limits, use a P type filter, whose class (1, 2 or 3) must be chosen according to the outcome of risk assessment.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

FG 06

SECTION 8. Exposure controls/personal protection ... / >>

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

In the case of prolonged contact with the product, protect the hands with penetration-resistant work gloves (see standard EN 374).

Work glove material must be chosen according to the use process and the products that may form. Latex gloves may cause sensitivity reactions.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

Use a type P filtering facemask, whose class (1, 2 or 3) and effective need, must be defined according to the outcome of risk assessment (see standard EN 149).

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	powder	
Colour	grey	
Odour	odourless	
Melting point / freezing point	not available	
Initial boiling point	not applicable	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	not applicable	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	12	
Kinematic viscosity	not available	
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1050-1150	g/dm ³
Relative vapour density	not available	
Particle characteristics	not available	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Granulometry < 0.8 mm

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

HYDRATED LIME

Stable in normal conditions of use and storage.

PORTLAND CEMENT CLINKER

When mixed with water, it hardens to form a stable mass.

FG 06

SECTION 10. Stability and reactivity ... / >>

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

HYDRATED LIME

Stable in normal conditions of use and storage.

PORTLAND CEMENT CLINKER

The compound is stable in the conditions of use and storage, if kept dry.

When wet, it can react with acids, ammonium salts, aluminum and other non-noble metals.

10.3. Possibility of hazardous reactions

The powders are potentially explosive when mixed with air.

HYDRATED LIME

Develops hydrogen on contact with: aluminium,brass,moisture.

Reacts with: carbon dioxide.

10.4. Conditions to avoid

Avoid environmental dust build-up.

HYDRATED LIME

Decomposes if exposed to: moisture,moist air.

PORTLAND CEMENT CLINKER

Moisture can cause lumps and quality loss.

10.5. Incompatible materials

HYDRATED LIME

Avoid contact with: acids.

PORTLAND CEMENT CLINKER

Incompatible with acids, ammonium salts, aluminum, alkaline metals and alkaline earth metals.

10.6. Hazardous decomposition products

HYDRATED LIME

Develops hydrogen on contact with: aluminium,brass,moisture.

PORTLAND CEMENT CLINKER

Develops hydrogen in contact with aluminum powder.

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

Not classified (no significant component)

ATE (Oral) of the mixture:

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

FG 06**SECTION 11. Toxicological information ... / >>**

HYDRATED LIME
LD50 (Dermal): > 2500 mg/kg
LD50 (Oral): > 2000 mg/kg

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

HYDRATED LIME
LC50 - for Fish > 160 mg/l/96h
EC50 - for Crustacea > 49,1 mg/l/48h
EC50 - for Algae / Aquatic Plants > 184,57 mg/l/72h
Chronic NOEC for Crustacea 32 mg/l
Chronic NOEC for Algae / Aquatic Plants 48 mg/l

12.2. Persistence and degradability

HYDRATED LIME
Solubility in water 1844,9 mg/l
Degradability: information not available

FG 06**SECTION 12. Ecological information ... / >>****12.3. Bioaccumulative potential**

Information not available

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessmentOn the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.**12.6. Endocrine disrupting properties**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

SECTION 14. Transport information ... / >>

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Contained substance</u>		
Point	75	Calcium carbonate
Point	47	PORTLAND CEMENT CLINKER
		REACH Reg.: 02-2119682167-31-0000

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)
On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)
None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:
None

Substances subject to the Rotterdam Convention:
None

Substances subject to the Stockholm Convention:
None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

REACH restriction 75 only applies to tattoo inks. Not applicable to the relevant identified uses of the product.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Eye Dam. 1	Serious eye damage, category 1
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1B	Skin sensitization, category 1B
H318	Causes serious eye damage.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.

Use descriptor system:
SU 19 Building and construction work

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)

SECTION 16. Other information ... / >>

- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

FG 06**CALCULATION METHODS FOR CLASSIFICATION**

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.