

**LG 01****Safety Data Sheet**

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

**SECTION 1. Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Code: **1706010002**  
Product name: **LG 01**  
UFI: **RH50-A0WA-P00F-00YD**

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Intended use: **Gray smoothing plaster for concrete**

| Identified Uses | Industrial | Professional   | Consumer       |
|-----------------|------------|----------------|----------------|
| <b>BUILDING</b> | -          | <b>SU: 19.</b> | <b>SU: 19.</b> |

**Product to be mixed with water for application on buildings.  
Product for craft and private use.  
Any other use is not recommended.**

**1.3. Details of the supplier of the safety data sheet**

Name: **FORNACI CALCE GRIGOLIN S.p. A.**  
Full address: **Via Foscarini, 2**  
District and Country: **31040 Nervesa della Battaglia (TV) Italy**  
Tel.: **+39 0422 5261**  
Fax: **+39 0422 526299**

e-mail address of the competent person responsible for the Safety Data Sheet: **info@fornacigrigolin.it**

**1.4. Emergency telephone number**

For urgent inquiries refer to: **HEALTH EMERGENCY - 112**

**SECTION 2. Hazards identification****2.1. Classification of the substance or mixture**

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

**Hazard classification and indication:**

|  |      |                                      |
|--|------|--------------------------------------|
| Serious eye damage, category 1                               | H318 | Causes serious eye damage.           |
| Skin irritation, category 2                                  | H315 | Causes skin irritation.              |
| Specific target organ toxicity - single exposure, category 3 | H335 | May cause respiratory irritation.    |
| Skin sensitization, category 1B                              | H317 | May cause an allergic skin reaction. |

**2.2. Label elements**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



**LG 01****SECTION 2. Hazards identification ... / >>**

Signal words: Danger

Hazard statements:

**H318** Causes serious eye damage.  
**H315** Causes skin irritation.  
**H335** May cause respiratory irritation.  
**H317** May cause an allergic skin reaction.

Precautionary statements:

**P101** If medical advice is needed, have product container or label at hand.  
**P102** Keep out of reach of children.  
**P261** Avoid breathing dust.  
**P280** Wear protective gloves / face protection.  
**P302+P352** IF ON SKIN: Wash with plenty of soap and water.  
**P304+P340** IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
**P305+P351+P338** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
**P310** Immediately call a POISON CENTER / doctor / . . .  
**P403+P233** Store in a well-ventilated place. Keep container tightly closed.

**Contains:** PORTLAND CEMENT CLINKER  
HYDRATED LIME

**2.3. Other hazards**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

The mixture has a low chromate content. After adding water the soluble chromium (VI) content is at most 2 ppm on the dry product.

To maintain a low chromate content, store it properly, in dry conditions, respecting the maximum expected storage terms.

The percentage of respirable crystalline silicon oxide is less than 1%. Therefore the product is not subject to identification. However it is advisable to use respiratory protection.

**SECTION 3. Composition/information on ingredients****3.2. Mixtures**

Contains:

| Identification                 | x = Conc. %           | Classification (EC) 1272/2008 (CLP)  |
|--------------------------------|-----------------------|--|
| <b>PORTLAND CEMENT CLINKER</b> |                       |  |
| INDEX                          | $20 \leq x < 30$      | <b>Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, Skin Sens. 1B H317</b> |
| EC                             | 266-043-4             |  |
| CAS                            | 65997-15-1            |  |
| REACH Reg.                     | 02-2119682167-31-0000 |  |
| <b>HYDRATED LIME</b>           |                       |  |
| INDEX                          | $1 \leq x < 4$        | <b>Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335</b>                     |
| EC                             | 215-137-3             |  |
| CAS                            | 1305-62-0             |  |
| REACH Reg.                     | 01-2119475151-45-0267 |  |

The full wording of hazard (H) phrases is given in section 16 of the sheet.

**SECTION 4. First aid measures****4.1. Description of first aid measures**

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

**SKIN:** Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again.

**INHALATION:** Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

**SECTION 4. First aid measures ... / >>**

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

**4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

**SECTION 5. Firefighting measures****5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

None in particular.

**5.2. Special hazards arising from the substance or mixture****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Do not breathe combustion products. The product is combustible and, when the powder is released into the air in sufficient concentrations and in the presence of a source of ignition, it can create explosive mixtures with air. Fires may start or get worse by leakage of the solid product from the container, when it reaches high temperatures or through contact with sources of ignition.

**5.3. Advice for firefighters****GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

If there are no contraindications, spray powder with water to prevent the formation of dust.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

**6.2. Environmental precautions**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

**6.3. Methods and material for containment and cleaning up**

Collect the leaked product and place it in containers for recovery or disposal. If there are no contraindications, use jets of water to eliminate product residues.

Make sure the leakage site is well aired. Evaluate the compatibility of the container to be used, by checking section 10. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage****7.1. Precautions for safe handling**

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

**SECTION 7. Handling and storage ... / >>**

**7.2. Conditions for safe storage, including any incompatibilities**

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

**7.3. Specific end use(s)**

Information not available

**SECTION 8. Exposure controls/personal protection**

**8.1. Control parameters**

Regulatory References:

|     |                |  |
|-----|----------------|--|
| FRA | France         | Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS   |
| HRV | Hrvatska       | Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)  |
| GBR | United Kingdom | EH40/2005 Workplace exposure limits (Fourth Edition 2020)  |
| EU  | OEL EU         | Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC. |
|     | TLV-ACGIH      | ACGIH 2022   |

**PORTLAND CEMENT CLINKER**

**Threshold Limit Value**

| Type      | Country | TWA/8h |     | STEL/15min |     | Remarks / Observations |
|-----------|---------|--------|-----|------------|-----|------------------------|
|           |         | mg/m3  | ppm | mg/m3      | ppm |                        |
| TLV-ACGIH |         | 1      |     |            |     | RESP                   |

**HYDRATED LIME**

**Threshold Limit Value**

| Type      | Country | TWA/8h |     | STEL/15min |     | Remarks / Observations |
|-----------|---------|--------|-----|------------|-----|------------------------|
|           |         | mg/m3  | ppm | mg/m3      | ppm |                        |
| VLEP      | FRA     | 5      |     |            |     |                        |
| GVI/KGVI  | HRV     | 5      |     |            |     |                        |
| WEL       | GBR     | 5      |     |            |     |                        |
| OEL       | EU      | 5      |     |            |     |                        |
| TLV-ACGIH |         | 5      |     |            |     |                        |

**Predicted no-effect concentration - PNEC**

|  |      |         |
|--|------|---------|
| Normal value in fresh water                  | 0,49 | mg/l    |
| Normal value in marine water                 | 0,32 | mg/l    |
| Normal value for water, intermittent release | 0,49 | mg/l    |
| Normal value of STP microorganisms           | 3    | mg/l    |
| Normal value for the terrestrial compartment | 1080 | mg/kg/d |

**Health - Derived no-effect level - DNEL / DMEL**

| Route of exposure | Effects on consumers |                |               | Effects on workers |             |                |               |                  |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
|                   | Acute local          | Acute systemic | Chronic local | Chronic systemic   | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Inhalation        | 4                    |                | 1             |                    | 4           |                | 1             |                  |
|                   | mg/m3                |                | mg/m3         |                    | mg/m3       |                | mg/m3         |                  |

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ;

MED = medium hazard ; HIGH = high hazard.

During the risk assessment process, it is essential to take into consideration the ACGIH occupational exposure levels for inert particulate not otherwise classified (PNOC respirable fraction: 3 mg/m3; PNOC inhalable fraction: 10 mg/m3). For values above these limits, use a P type filter, whose class (1, 2 or 3) must be chosen according to the outcome of risk assessment.

**8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

# LG 01

## SECTION 8. Exposure controls/personal protection ... / >>

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

### HAND PROTECTION

In the case of prolonged contact with the product, protect the hands with penetration-resistant work gloves (see standard EN 374).

Work glove material must be chosen according to the use process and the products that may form. Latex gloves may cause sensitivity reactions.

### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

### RESPIRATORY PROTECTION

Use a type P filtering facemask, whose class (1, 2 or 3) and effective need, must be defined according to the outcome of risk assessment (see standard EN 149).

### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

| Properties                             | Value          | Information       |
|--|----------------|-------------------|
| Appearance                             | powder         |                   |
| Colour                                 | grey           |                   |
| Odour                                  | odourless      |                   |
| Melting point / freezing point         | not available  |                   |
| Initial boiling point                  | not applicable |                   |
| Flammability                           | not available  |                   |
| Lower explosive limit                  | not available  |                   |
| Upper explosive limit                  | not available  |                   |
| Flash point                            | not applicable |                   |
| Auto-ignition temperature              | not available  |                   |
| Decomposition temperature              | not available  |                   |
| pH                                     | 12             |                   |
| Kinematic viscosity                    | not available  |                   |
| Solubility                             | not available  |                   |
| Partition coefficient: n-octanol/water | not available  |                   |
| Vapour pressure                        | not available  |                   |
| Density and/or relative density        | 1300-1400      | g/dm <sup>3</sup> |
| Relative vapour density                | not available  |                   |
| Particle characteristics               | not available  |                   |

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

Information not available

#### 9.2.2. Other safety characteristics

Granulometry < 0.6 mm

## SECTION 10. Stability and reactivity

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### PORTLAND CEMENT CLINKER

When mixed with water, it hardens to form a stable mass.

#### HYDRATED LIME

Stable in normal conditions of use and storage.

**SECTION 10. Stability and reactivity** ... / >>**10.2. Chemical stability**

The product is stable in normal conditions of use and storage.

**PORTLAND CEMENT CLINKER**

The compound is stable in the conditions of use and storage, if kept dry.  
When wet, it can react with acids, ammonium salts, aluminum and other non-noble metals.

**HYDRATED LIME**

Stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions**

The powders are potentially explosive when mixed with air.

**HYDRATED LIME**

Develops hydrogen on contact with: aluminium,brass,moisture.  
Reacts with: carbon dioxide.

**10.4. Conditions to avoid**

Avoid environmental dust build-up.

**PORTLAND CEMENT CLINKER**

Moisture can cause lumps and quality loss.

**HYDRATED LIME**

Decomposes if exposed to: moisture,moist air.

**10.5. Incompatible materials****PORTLAND CEMENT CLINKER**

Incompatible with acids, ammonium salts, aluminum, alkaline metals and alkaline earth metals.

**HYDRATED LIME**

Avoid contact with: acids.

**10.6. Hazardous decomposition products****PORTLAND CEMENT CLINKER**

Develops hydrogen in contact with aluminum powder.

**HYDRATED LIME**

Develops hydrogen on contact with: aluminium,brass,moisture.

**SECTION 11. Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

|                                  |   |
|----------------------------------|---|
| ATE (Inhalation) of the mixture: | Not classified (no significant component) |
| ATE (Oral) of the mixture:       | Not classified (no significant component) |
| ATE (Dermal) of the mixture:     | Not classified (no significant component) |

**LG 01****SECTION 11. Toxicological information ... / >>**

HYDRATED LIME  
LD50 (Dermal): > 2500 mg/kg  
LD50 (Oral): > 2000 mg/kg

**SKIN CORROSION / IRRITATION**

Causes skin irritation

**SERIOUS EYE DAMAGE / IRRITATION**

Causes serious eye damage

**RESPIRATORY OR SKIN SENSITISATION**

Sensitising for the skin

**GERM CELL MUTAGENICITY**

Does not meet the classification criteria for this hazard class

**CARCINOGENICITY**

Does not meet the classification criteria for this hazard class

**REPRODUCTIVE TOXICITY**

Does not meet the classification criteria for this hazard class

**STOT - SINGLE EXPOSURE**

May cause respiratory irritation

**STOT - REPEATED EXPOSURE**

Does not meet the classification criteria for this hazard class

**ASPIRATION HAZARD**

Does not meet the classification criteria for this hazard class

**11.2. Information on other hazards**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

**SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

**12.1. Toxicity**

HYDRATED LIME  
LC50 - for Fish > 160 mg/l/96h  
EC50 - for Crustacea > 49,1 mg/l/48h  
EC50 - for Algae / Aquatic Plants > 184,57 mg/l/72h  
Chronic NOEC for Crustacea 32 mg/l  
Chronic NOEC for Algae / Aquatic Plants 48 mg/l

**12.2. Persistence and degradability**

HYDRATED LIME  
Solubility in water 1844,9 mg/l  
Degradability: information not available

**LG 01****SECTION 12. Ecological information ... / >>****12.3. Bioaccumulative potential**

Information not available

**12.4. Mobility in soil**

Information not available

**12.5. Results of PBT and vPvB assessment**On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.**12.6. Endocrine disrupting properties**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

**12.7. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations****13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

**14.1. UN number or ID number**

not applicable

**14.2. UN proper shipping name**

not applicable

**14.3. Transport hazard class(es)**

not applicable

**14.4. Packing group**

not applicable

**14.5. Environmental hazards**

not applicable

**14.6. Special precautions for user**

not applicable



**LG 01****SECTION 14. Transport information ... / >>****14.7. Maritime transport in bulk according to IMO instruments**

Information not relevant

**SECTION 15. Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

| <u>Contained substance</u> |    |                                   |
|----------------------------|----|-----------------------------------|
| Point                      | 75 | Calcium carbonate                 |
| Point                      | 47 | PORTLAND CEMENT CLINKER           |
|                            |    | REACH Reg.: 02-2119682167-31-0000 |

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors  
not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

REACH restriction 75 only applies to tattoo inks. Not applicable to the relevant identified uses of the product.

**15.2. Chemical safety assessment**

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

|                      |  |
|----------------------|--|
| <b>Eye Dam. 1</b>    | Serious eye damage, category 1                               |
| <b>Skin Irrit. 2</b> | Skin irritation, category 2                                  |
| <b>STOT SE 3</b>     | Specific target organ toxicity - single exposure, category 3 |
| <b>Skin Sens. 1B</b> | Skin sensitization, category 1B                              |
| <b>H318</b>          | Causes serious eye damage.                                   |
| <b>H315</b>          | Causes skin irritation.                                      |
| <b>H335</b>          | May cause respiratory irritation.                            |
| <b>H317</b>          | May cause an allergic skin reaction.                         |

Use descriptor system:

**SU 19** Building and construction work

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)

**SECTION 16. Other information ... / >>**

- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

# LG 01

## CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.