



FUGASTYLE[®] DTG ACIDO



Acid-based cleaner for removing cement residues from ceramic tiles and equipment.

Product description

Specific acid detergent for cleaning and descaling floors and surfaces.

Fields of application

- Effectively removes limescale, lime and cement residues from acid-tolerant surfaces (ceramics, tiles, stainless steel).

DTG ACIDO

Preparation

Ready-to-use product that can be used immediately without additional dilution. Before use, briefly shake the product inside the package to even out the consistency of the dispersion. The product is homogeneous and free of lumps or thickening.

After use, the excess quantity can be stored for later use by closing the pack with its cap.

Methods of application

For the removal of limescale deposits use the product pure. Rinse after use.

Indicative consumption

The consumption of BASEFORTE® DTG ACID depends on the state of the substrate.

In general:

100-200 g/m²

Technical advice

- Never transfer the product into anonymous containers.
- First carry out a test in a small, enclosed area.
- If used to remove efflorescence from fillers, dilute DTG ACIDO up to 70% for dark colours and 50% for light colours.
- Check that the substrates are resistant to acid cleaning.

Operating times

The product must act on the floor for at least 10-15 minutes, after which it can be rinsed off with plenty of water.

Supply and storage

BASEFORTE® DTG ACID is supplied in 1 kg and 10 kg packages.

Store at a temperature between +5°C and +30°C in the original sealed containers. Under these conditions the shelf life of the stored product is more than one year.

Specifications

Cleaning of substrates by applying an acid-based detergent capable of removing traces of limestone, lime and cement from any type of non-absorbent surface, such as BASEFORTE® DTG ACIDO by Fornaci Calce Grigolin.

Warnings

Use the product according to the instructions in this technical data sheet and on the label.

DTG ACIDO

TECHNICAL DATA	PERFORMANCE
Appearance	liquid
Colour	colourless
pH	2,2 ± 0,5
Specific weight	approx. 1080 g/l
Biodegradability	compliant with EC Reg 648/2004
Phosphorus content	1%

v. 10/2021

I dati riportati si riferiscono alle prove di Controllo Qualità in condizioni ambientali normalizzate. Applicazioni pratiche di cantiere a seconda delle condizioni di esercizio possono rilevare dati sensibilmente modificati, pertanto le informazioni presenti nella Scheda hanno valore puramente indicativo in quanto l'utilizzatore deve sempre verificare l'idoneità nell'utilizzo. Fornaci Calce Grigolin S.p.A. si riserva di apportare modifiche tecniche di qualsiasi genere senza alcun preavviso.